

Draft Amendment Under 37 C.F.R. § 1.111  
U.S. Appl. No.: 10/784,942

Attorney Docket # Q79954

### AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application:

#### **LISTING OF CLAIMS:**

1. (Currently Amended) An apparatus adapted to make an electrical connection with a first electronic unit having a first edge portion and first terminals disposed along said first edge portion, said apparatus comprising:

a first supporting member; and

a first connector supported by said first supporting member, said first connector having a body elongated in a longitudinal direction and second terminals disposed along said longitudinal direction, wherein:

said first connector is adapted to slidably guide said first edge portion of said first electronic unit along said longitudinal direction to a first fully inserted position such that each one of said first terminals faces a respective one of said second terminals; and

said first connector includes a first lock mechanism locking said first edge portion of said first electronic unit at said first fully inserted position and connecting said first terminals and said second terminals electrically.

2. (Cancelled)

Draft Amendment Under 37 C.F.R. § 1.111  
U.S. Appln. No.: 10/784,942

Attorney Docket # Q79954

3. (Original) The apparatus according to claim 1, wherein said supporting member includes a circuit board.

4. (Original) The apparatus according to claim 1, wherein a direction of a cooling airflow is substantially parallel to said longitudinal direction of said first connector.

5. (Currently Amended) The apparatus according to claim 1, further comprising a housing having a front portion, a rear portion and ~~an~~ a front opening in said front portion, wherein

said first supporting member and said first connector are arranged between said front portion and said rear portion of said housing.

6. (Original) The apparatus according to claim 5, wherein said longitudinal direction of said first connector is substantially parallel to a direction from said front portion to said rear portion of said housing.

7. (Original) The apparatus according to claim 6, wherein said housing further has a fan providing a cooling airflow in a direction from said front portion to said rear portion of said housing.

Dr. ft Amendment Under 37 C.F.R. § 1.111  
U.S. Appln. No.: 10/784,942

Attorney Docket # Q79954

8. (Original) The apparatus according to claim 5, wherein said first supporting member is substantially perpendicular to said front portion of said housing.

9. (Currently Amended) The apparatus according to claim 1, wherein  
said first electronic unit further has a second edge portion substantially parallel and opposite to said first edge portion and ~~forth~~ fourth terminals disposed along said second edge portion,

said apparatus further includes a second supporting member and a second connector;  
said second connector has a body elongated in a longitudinal direction and third terminals disposed along said longitudinal direction of said second connector,

said second connector is supported by said second supporting member and arranged substantially parallel and opposite to said first connector, and

said second connector is adapted to slidably guide said second edge portion of said first electronic unit along said longitudinal direction of said second connector to said first fully inserted position such that each one of said third terminals faces a respective one of said ~~forth~~ fourth terminals.

10. (Currently Amended) The apparatus according to claim 9, wherein ~~said first connector includes a first lock mechanism locking said first edge portion of said first electronic unit at said first fully inserted position and connecting said first terminals and said second terminals electrically, and said second connector includes a second lock mechanism locking said~~

Draft Amendment Under 37 C.F.R. § 1.111  
U.S. Appln. No.: 10/784,942

Attorney Docket # Q79954

second edge portion of said first electronic unit at said first fully inserted position and connecting said third terminals and said ~~fourth~~ fourth terminals electrically.

11. (Original) The apparatus according to claim 9, wherein each of said first supporting member and said second supporting member includes a circuit board.

12. (Original) The apparatus according to claim 9, wherein a direction of a cooling airflow is substantially parallel to said longitudinal direction of said first connector.

13. (Original) The apparatus according to claim 9, further comprising a housing having a front portion, a rear portion and a front opening in said front portion, wherein said first supporting member, said second supporting member, said first connector and said second connector are arranged between said front portion and said rear portion of said housing.

14. (Original) The apparatus according to claim 13, wherein said longitudinal direction of said first connector is substantially parallel to a direction from said front portion to said rear portion of said housing.

15. (Original) The apparatus according to claim 14, wherein said housing further has a fan providing a cooling airflow in a direction from said front portion to said rear portion.

Dr. ft Amendment Under 37 C.F.R. § 1.111  
U.S. Appln. No.: 10/784,942

Attorney Docket # Q79954

16. (Original) The apparatus according to claim 13, wherein said first and second supporting members are substantially perpendicular to said front portion of said housing.

17. (Original) The apparatus according to claim 9, wherein said first supporting member and said second supporting member are adapted to be electrically connected through said first electronic unit.

18. (Original) The apparatus according to claim 9, wherein said first and second supporting members are parallel to each other.

19. (Original) The apparatus according to claim 18, wherein said first and second connectors are adapted to support said first electronic unit such that said first electronic unit is substantially perpendicular to said first and second supporting members.

20. (Currently Amended) The apparatus according to claim 1, wherein:  
said apparatus is further adapted to make an electrical connection with a second electronic unit having a third edge portion and fifth terminals disposed along said third edge portion;

said apparatus further comprises a third connector supported by said first supporting member;

Dr ft Amendment Under 37 C.F.R. § 1.111  
U.S. Appln. No.: 10/784,942

Attorney Docket # Q79954

said third connector has a body elongated in a longitudinal direction and sixth terminals disposed along said longitudinal direction of said third connector<sub>31</sub>

said third connector is adapted to slidably guide said third edge portion of said second electronic unit along said longitudinal direction of said third connector to a second fully inserted position such that each one of said fifth terminals faces a respective one of said sixth terminals<sub>32</sub>

said first electronic unit is slidably inserted into said first connector in a first direction along said longitudinal direction of said first connector<sub>31</sub> and

said second electronic unit is slidably inserted into said third connector in a second direction substantially opposite to said first direction.

21. (Original) The apparatus according to claim 20, said third connector is arranged substantially parallel to said first connector.

22. (Original) The apparatus according to claim 20, further comprising a housing having a front portion, a rear portion, a front opening on said front portion and a rear opening on said rear portion, wherein

said first supporting member, said first connector and said third connector are arranged between said front portion and said rear portion of said housing.

23. (Currently Amended) The apparatus according to claim 9, wherein:

Draft Amendment Under 37 C.F.R. § 1.111  
U.S. Appl. No.: 10/784,942

Attorney Docket # Q79954

said apparatus is further adapted to make an electrical connection with a second electronic unit having a third edge portion and fifth terminals disposed along said third edge portion;

said apparatus further comprises a third connector;

said third connector has a body elongated in a longitudinal direction and sixth terminals disposed along said longitudinal direction of said third connector;

said third connector is supported by said first supporting ~~members~~ member;

said third connector is adapted to slidably guide a third edge portion of said second electronic unit along said longitudinal direction of said third connector to a second fully inserted position such that each one of said fifth terminals faces a respective one of said sixth terminals;  
and

said first electronic unit is slidably inserted into said first and second connectors in a first direction along said longitudinal direction of said first connector; and

said second electronic unit is slidably inserted into said third connector in a second direction substantially opposite to said first direction.

24. (Original) The apparatus according to claim 23, further comprising a housing having a front portion, a rear portion, a front opening in said front portion and a rear opening in said rear portion, wherein

said first and second supporting members and said first, second and third connectors are arranged between said front portion and said rear portion of said housing.

Drift Amendment Under 37 C.F.R. § 1.111  
U. S. Appln. No.: 10/784,942

Attorney Docket # Q79954

25. (Original) The apparatus according to claim 23, wherein said first and second supporting members are parallel to each other, and said third connector is arranged substantially parallel to said first connector.

26. (Currently Amended) The apparatus according to claim 1, ~~further comprising:~~  
wherein said first electronic unit is connected to said first connector.

27. (New) An apparatus adapted to make an electrical connection with a first electronic unit having a first edge portion and first terminals disposed along said first edge portion, said apparatus comprising:

a first supporting member; and

a first connector supported by said first supporting member, said first connector having a body elongated in a longitudinal direction and second terminals disposed along said longitudinal direction, wherein:

said first connector is adapted to slidably guide said first edge portion of said first electronic unit along said longitudinal direction to a first fully inserted position such that each one of said first terminals faces a respective one of said second terminals;

said first electronic unit further has a second edge portion substantially parallel and opposite to said first edge portion and fourth terminals disposed along said second edge portion;

said apparatus further includes a second supporting member and a second connector;



Draft Amendment Under 37 C.F.R. § 1.111  
U.S. Appl. No.: 10/784,942

Attorney Docket # Q79954

said second connector has a body elongated in a longitudinal direction and third terminals disposed along said longitudinal direction of said second connector;

said second connector is supported by said second supporting member and arranged substantially parallel and opposite to said first connector;

said second connector is adapted to slidably guide said second edge portion of said first electronic unit along said longitudinal direction of said second connector to said first fully inserted position such that each one of said third terminals faces a respective one of said fourth terminals;

said first connector includes a first lock mechanism locking said first edge portion of said first electronic unit at said first fully inserted position and connecting said first terminals and said second terminals electrically; and

said second connector includes a second lock mechanism locking said second edge portion of said first electronic unit at said first fully inserted position and connecting said third terminals and said fourth terminals electrically.

28. (New) An apparatus adapted to make an electrical connection with a first electronic unit having a first edge portion and first terminals disposed along said first edge portion, said apparatus comprising:

a first supporting member; and

Draft Amendment Under 37 C.F.R. § 1.111  
U.S. Appl. No.: 10/784,942

Attorney Docket # Q79954

a first connector supported by said first supporting member, said first connector having a body elongated in a longitudinal direction and second terminals disposed along said longitudinal direction, wherein:

said first connector is adapted to slidably guide said first edge portion of said first electronic unit along said longitudinal direction to a first fully inserted position such that each one of said first terminals faces a respective one of said second terminals;

said first electronic unit further has a second edge portion substantially parallel and opposite to said first edge portion and fourth terminals disposed along said second edge portion;

said apparatus further includes a second supporting member and a second connector;

said second connector has a body elongated in a longitudinal direction and third terminals disposed along said longitudinal direction of said second connector;

said second connector is supported by said second supporting member and arranged substantially parallel and opposite to said first connector, and

said second connector is adapted to slidably guide said second edge portion of said first electronic unit along said longitudinal direction of said second connector to said first fully inserted position such that each one of said third terminals faces a respective one of said fourth terminals,

said apparatus further comprising a housing having a front portion, a rear portion and a front opening in said front portion, wherein said first supporting member, said second supporting member, said first connector and said second connector are arranged between said front portion and said rear portion of said housing.

Draft Amendment Under 37 C.F.R. § 1.111  
U. S. Appln. No.: 10/784,942

Attorney Docket # Q79954

29. (New) The apparatus according to claim 28, wherein said longitudinal direction of said first connector is substantially parallel to a direction from said front portion to said rear portion of said housing.

30. (New) The apparatus according to claim 29, wherein said housing further has a fan providing a cooling airflow in a direction from said front portion to said rear portion.

31. (New) The apparatus according to claim 28, wherein said first and second supporting members are substantially perpendicular to said front portion of said housing.

32. (New) An apparatus adapted to make an electrical connection with a first electronic unit having a first edge portion and first terminals disposed along said first edge portion, said apparatus comprising:

a first supporting member; and

a first connector supported by said first supporting member, said first connector having a body elongated in a longitudinal direction and second terminals disposed along said longitudinal direction, wherein:

said first connector is adapted to slidably guide said first edge portion of said first electronic unit along said longitudinal direction to a first fully inserted position such that each one of said first terminals faces a respective one of said second terminals;

Drift Amendment Under 37 C.F.R. § 1.111  
U. S. Appln. No.: 10/784,942

Attorney Docket # Q79954

said apparatus is further adapted to make an electrical connection with a second electronic unit having a third edge portion and fifth terminals disposed along said third edge portion;

said apparatus further comprises a third connector supported by said first supporting member;

said third connector has a body elongated in a longitudinal direction and sixth terminals disposed along said longitudinal direction of said third connector;

said third connector is adapted to slidably guide said third edge portion of said second electronic unit along said longitudinal direction of said third connector to a second fully inserted position such that each one of said fifth terminals faces a respective one of said sixth terminals;

said first electronic unit is slidably inserted into said first connector in a first direction along said longitudinal direction of said first connector; and

said second electronic unit is slidably inserted into said third connector in a second direction substantially opposite to said first direction.

33. (New) The apparatus according to claim 32, said third connector is arranged substantially parallel to said first connector.

34. (New) The apparatus according to claim 32, further comprising a housing having a front portion, a rear portion, a front opening on said front portion and a rear opening on said rear portion, wherein

Drift Amendment Under 37 C.F.R. § 1.111  
U. S. Appln. No.: 10/784,942

Attorney Docket # Q79954

said first supporting member, said first connector and said third connector are arranged between said front portion and said rear portion of said housing.

35. (New) An apparatus adapted to make an electrical connection with a first electronic unit having a first edge portion and first terminals disposed along said first edge portion, said apparatus comprising:

a first supporting member; and

a first connector supported by said first supporting member, said first connector having a body elongated in a longitudinal direction and second terminals disposed along said longitudinal direction, wherein:

said first connector is adapted to slidably guide said first edge portion of said first electronic unit along said longitudinal direction to a first fully inserted position such that each one of said first terminals faces a respective one of said second terminals;

said apparatus is further adapted to make an electrical connection with a second electronic unit having a third edge portion and fifth terminals disposed along said third edge portion;

said apparatus further comprises a third connector;

said third connector has a body elongated in a longitudinal direction and sixth terminals disposed along said longitudinal direction of said third connector;

said third connector is supported by said first supporting member;

Draft Amendment Under 37 C.F.R. § 1.111  
U.S. Appl. No.: 10/784,942

Attorney Docket # Q79954

said third connector is adapted to slidably guide a third edge portion of said second electronic unit along said longitudinal direction of said third connector to a second fully inserted position such that each one of said fifth terminals faces a respective one of said sixth terminals;

said first electronic unit is slidably inserted into said first and second connectors in a first direction along said longitudinal direction of said first connector; and

said second electronic unit is slidably inserted into said third connector in a second direction substantially opposite to said first direction.

36. (New) The apparatus according to claim 35, further comprising a housing having a front portion, a rear portion, a front opening in said front portion and a rear opening in said rear portion, wherein

said first and second supporting members and said first, second and third connectors are arranged between said front portion and said rear portion of said housing.

37. (New) The apparatus according to claim 35, wherein said first and second supporting members are parallel to each other, and said third connector is arranged substantially parallel to said first connector.

Draft Amendment Under 37 C.F.R. § 1.111  
U. S. Appln. No.: 10/784,942

Attorney Docket # Q79954

38. (New) An apparatus adapted to make an electrical connection with a first electronic unit having a first edge portion and first terminals disposed along said first edge portion, said apparatus comprising:

- a housing comprising side walls, a front wall and a rear wall;
- a fan mounted on the rear portion aligned to direct a cooling airflow in a first direction;
- a second fan mounted on the front wall aligned to direct a second cooling airflow in the first direction;

- a first supporting member arranged in the housing; and
- a first connector on said first supporting member, said first connector comprising a body elongated in a longitudinal direction and second terminals disposed along said longitudinal direction, wherein:

- said first connector is adapted to slidably guide said first edge portion of said first electronic unit along said longitudinal direction to a first fully inserted position such that each one of said first terminals faces a respective one of said second terminals;

- the first direction of cooling airflow is along the longitudinal direction; and

- the rear wall and front wall are parallel to each other and perpendicular to the longitudinal direction.

Draft Amendment Under 37 C.F.R. § 1.111  
U.S. Appl. No.: 10/784,942

Attorney Docket # Q79954

**AMENDMENTS TO FIGURES**

Please add new Figures 7a and 8a, which are attached hereto.